



+4°C

Blood Bank Refrigerator

(Forced-air Cooling System)

Model: MBC-4V208



Applications

Blood bank refrigerators are specially designed to store blood bags and blood-derived products.

Features

- Microprocessor control, ensure the inside temperature of $4^{\circ}\text{C}\pm 1^{\circ}\text{C}$ accuracy is 0.1°C
- Suggested ambient temperature: $+10\sim 32^{\circ}\text{C}$.
- Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.
- Toughened glass door with heater to avoid condensation.
- Wide available voltage range: $220\text{V}\pm 10\%$.

Security

- Safety door lock and controller password to prevent unauthorized access.
- 72h built-in backup battery to power the controller and save temp. data when power failure or system error.
- Visual and audible alarm system.
- Power failure protection: turn-on delay of the cooling system after power failure.
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

- Special designed service-free drainage system, ensure no water in the cabinet.
- Adjustable shelves and blood baskets for easy storage.
- Casters with stoppers for easy moving and fixation.
- Auto on/off LED light with manual switch on the control panel.
- Auto on/off cooling fan to prevent cold air from leaking out when the door is opening.



Specifications

Model NO.	MBC-4V208
Main Specifications	
Temperature Range	4 ± 1 °C
Ambient Temperature	10~32°C
Capacity (L/Cu. Ft.)	208 / 7.35
Interior Dimensions (W×D×H) mm	432×462×1055
Exterior Dimensions (W×D×H) mm	522×635×1530
Weight	98 kgs
Noise	48 dB
Max Loading of 450/400/300/200ml Blood Bag	132/156/192/240 Bags
Control and Power	
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	194 W
Electric Current	1.3 A
Power Consumption (kWh/24h)	2.4
Audible and Visual Alarms	
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Battery Error Alarm	Yes
Refrigeration	
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	EMBRACO / 1
Refrigerant / Weight	R134a / 96g
Cabinet	
Door (pcs)	Self-closing Foamed Heating Glass Door / 1
Inner Door (pcs)	PMMA / 4
Adjustable Shelf (pcs)	4
Basket (pcs)	12
Interior Cabinet Material	Stainless Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (δ45mm)
Door Lock	Yes
LED Lamp	Yes
Test Hole (pcs)	1
Castors (pcs)	4
Accessories	
Remote Alarm Port	Yes
Temperature Printer	Yes
USB Data Download Port	Optional
RS485 Port	Optional
Temperature Datalogger	Optional
Shipping	
Package	Plywood box with pallet
Shipping Weight	120 kgs
Shipping Size (W×D×H)	600×700×1680
Shipping Volume	0.71 CBM

* Due to continuous product upgrades, the above specifications are for reference only. For the latest specifications, please contact us.